



## Stealth Trapdoor

### OUT OF SIGHT

The Stealth Trapdoor Electriscreen was strategically engineered for use within multi-purpose environments in which the screen must disappear completely when not in use.

### MAXIMIZING PERFORMANCE

The Stealth is available with any of Stewart's front or rear materials. Our exclusive Tab-Guy™ tensioning system ensures a smooth and completely flat screen surface. A matte-black painted border, including 12" of black-drop (unless otherwise specified) provides a perfectly masked image area while absorbing any potential over-scan.

### THE STEWART DIFFERENCE

Stewart Filmscreen is synonymous for superior quality, custom craftsmanship and excellent customer service. Since every Stewart product is handcrafted, custom sizes and configurations are easily accommodated.



- » Electronically controlled trapdoor
- » Disappears completely when not in use
- » Available in front or rear models
- » Exclusive Tab-Guy™ tension system
- » Standard 12" painted black-drop
- » Includes high voltage switch

A screen is the centerpiece of your projection environment. Invest in quality craftsmanship and your screen will last you through a lifetime of technology. Contact the Stewart representative in your area today for more information on how to get a Stewart Filmscreen made especially for you!

**Stewart**

Filmscreen Corporation®  
California | Ohio | Denmark | Singapore




# Stealth Trapdoor

MAX IMAGE SIZE UP TO: 72 x 96

### CASE DIMENSIONS:

Case Height: 8.25  
Case Depth: 6



### SPECIFICATIONS:

Aluminum Housing/Case	Included
Electronically Controlled Trapdoor	Included
Case Color	White
Batten Color	Black, White
Tab-Guy™ Tensioning System	Included
Black-Matte Image Border	Included

(Standard 12" black-drop included unless otherwise specified)

### MATERIAL:

Front Projection Material	Included
Rear Projection Material - Flexible	Optional

### PERFORATIONS:

Microperf X <sup>2</sup>	Optional
Cinemaparf	Optional

### MOTOR:

120 Volt Motor (38 rpm - 1 amp)	Included
220 Volt Motor (32 rpm - 1 amp)	Optional

### CONTROL:

HVS (High Voltage Switch)	Included
LVC (Low Voltage Control)	Optional
STI (12 Volt Screen Trigger Interface)	Optional
IRR (Infrared Remote)	Optional
WRC (Wireless RF Remote Control)	Optional

### MOUNTING:

Recessed Ceiling Mount	Included
------------------------	----------

(Includes adjustable dry wall stops)

*ABT Trapdoor is available for larger venue applications*

### HDTV FORMAT - 16:9/1.78:1 ASPECT RATIO

Model No.	Diag	IMAGE		CASE Length	(lbs.) Weight
		Height	Width		
SEL082H	82	40.5	72	99	58
SEL092H	92	45	80	107	61
SEL100H	100	49	87	114	64
SEL110H	110	54	96	123	67

### NTSC FORMAT - 4:3/1.33:1 ASPECT RATIO

Model No.	Diag	IMAGE		CASE Length	(lbs.) Weight
		Height	Width		
SEL060V	60	36	48	75	48
SEL072V	72	43	57	84	52
SEL084V	84	50	67	94	56
SEL090V	90	54	72	99	58
SEL100V	100	60	80	107	61
SEL120V	120	72	96	121	68

Case length does not include 1" mounting bracket on both ends of housing.

Dimensions are specified in (") inches  
Specifications subject to change at any time without notice